

Starplast

uređaji za pročišćavanje otpadnih voda i spremnici



Uvoznik i distributer : Legomont d.o.o. www.legomont.hr

Tel: 021 533 176 Fax: 021 543 485 e-mail: legomont@legomont.hr

Mastolovci DEG ...



Mastolovci za odvajanje kuhinjskih ulja i masti koriste se za odvajanje i tretman otpadnih voda kuhinja, ribarnica, mesnica, restorana, menzi i sl. Mastolovci su izrađeni iz rotaciono lijevanog polietilena te omogućuju izravnu ugradnju u teren bez potrebe za dodatnim učvršćivanjem i betoniranjem.

Kontrolni otvor te otvor za pražnjenje mogu se proizvoditi produžecima na navoj. Prilikom ugradnje mastolovac je potrebno spojiti sa odzračnom cijevi. Održavanje se vrši uklanjanjem masti i taloga preko otvora za pražnjenje. Preporučuje se da pražnjenje obavlja ovlaštena tvrtka. Starplast mastolovci izrađeni su po Evropskoj normi UNI EN 1825 .



T3 - javna kanalizacija

Norma

UNI EN 1825/1-2

Dodatni pribor

PRO X 200/400/620
GRI Y 600
TPA Y 50
CHI Y 400-200
CHI Y 600-500

odabir mastolovaca prema:

OCTAGONAL "O"



COMPACT "K"



CORRUGATED "C"




MODULAR "M"



model	E.S.	odabir prema UNI 1825					Tehnički podaci					
	ekvivalent stanovnika	restorani broj obroka	obrada mesa i ribe broj radnih mjesta			protok	dimenzije	visina uređaja	visina ulaza i izlaza	Ø cijev		
	T3	CO	CO			l/s	cm	cm	cm	mm		
DEG O 150 ..	4	-	20			0,5	60x60	57	49/47	80		
DEG K 300 ..	10	-	45			1,0	95x64	62	52/50	110		
DEG K 400 ..	12	-	55			1,3	120x80	60	48/45	110		
DEG K 500 ..	14	-	70			1,5	120x80	70	58/55	110		
DEG C 800 ..	22	50	80			2,0	Ø 125	105	73/70	125		
DEG C 1200 ..	30	65	130			3,0	Ø 125	127	95/92	125		
DEG C 1600 ..	42	90	180			4,0	Ø 125	171	140/137	125		
DEG C 2000 ..	50	110	220			5,0	Ø 125	193	162/159	125		
DEG CC 3500 ..	60	230	300			7,0	Ø 180	149	127/124	125		
DEG CC 4000 ..	70	270	360			8,0	Ø 180	170	148/145	160		
DEG CC 4500 ..	80	310	400			9,0	Ø 180	191	169/166	160		
DEG CC 5000 ..	90	350	450			10,0	Ø 180	212	190/187	160		
DEGN 9000 ..	164	660	-	-	-	18,0	210x285	234	199/194	160		
DEGM 12000 ..	220	880	-	-	-	24,0	210x440	234	206/201	160		
DEGMN15000 ..	280	1100	-	-	-	30,0	210x465	234	199/194	160		
DEGM 18000 ..	330	1300	-	-	-	36,0	210x620	234	206/201	200		
DEGMN 21000 ..	380	1550	-	-	-	42,0	210x645	234	199/194	200		
DEGM 24000 ..	440	1750	-	-	-	48,0	210x800	234	206/201	200		

Separator ulja sa koalescentnim filterom

DEC ...



Norma

UNI EN 858 1-2

model	odabir separatora			Tehnički podaci			
	broj parkirnih mjesta	veliki natkrivene	površine otvorene	protok	dimenzije separatora Ø x h	visina ulaza/izlaza	Ø cijevi ulaza/izlaza
	n.	m ²	m ²	l/s	cm	cm	mm
DEC C 800 FX0 AS	17	700	350	2,0	125x114	73/70	125
DEC C 1200 FX0 AS	22	880	440	2,5	125x136	95/92	125
DEC C 1600 FX0 AS	28	1100	560	3,0	125x180	140/137	125
DEC C 2000 FX0 AS	35	1400	690	4,0	125x202	162/159	125
DEC C 3500 FX0 AS	55	2200	1100	6,0	180x158	127/124	125
DEC C 4000 FX0 AS	65	2600	1300	7,0	180x179	148/145	160
DEC C 4500 FX0 AS	76	3000	1500	8,0	180x200	169/166	160
DEC C 5000 FX0 AS	87	3500	1750	10,0	180x221	190/187	160
DEC N 9000 FX0 AS	150	6000	3000	16,0	210x285x234	199/195	160

Separatori za odvajanje neemulgiranih naftnih derivata namjenjeni su za odvajanje i tretman otpadnih voda parkirališta, garaža, autoservisa, radionica, pogona ...

Separatori su izrađeni iz rotaciono lijevanog polietilena te omogućuju izravnu ugradnju u teren bez potrebe za dodatnim učvršćivanjem i betoniranjem.

Kontrolni otvor te otvor za pražnjenje mogu se produživati produžecima na navoj. Prilikom ugradnje separator je potrebno spojiti sa odzračnom cijevi.

Održavanje se vrši uklanjanjem masti i taloga preko otvora za pražnjenje.

Preporučuje se da pražnjenje obavlja ovlaštena tvrtka.

Starplast separatori naftnih derivata izrađeni su po Evropskoj normi UNI EN 858 1-2 .

Spremnici SEI ...



Podzemni spremnici SEI izradeni su iz rotaciono lijevanog polietilena rebrastog profila. Koristimo ih za skladištenje vode, lož ulja.... Otporni su na temperature u rasponu od -60 do 60 C.

dodatni pribor

PRO X 400/500/620
GRI Y 600
TPA Y 50
CHI Y 400-200
CHI Y 500-400
CHI Y 600-500

skladištenje vode, lož ulja....

1000/5000 "C"



5000 "N"



12000/42000 "M"



jednodijelni


model	Tehnički podaci			otvor
	volumen	L x L	h	Ø
	lt	cm	cm	cm
SEI C 1000 AG	1000	Ø 125	105	400
SEI C 1200 AG	1300	Ø 125	127	400
SEI C 1800 AG	1800	Ø 125	171	400
SEI C 2000 AG	2050	Ø 125	193	400
SEI C 3500 AG	3350	Ø 180	149	400
SEI C 4000 AG	3900	Ø 180	170	400
SEI C 4500 AG	4400	Ø 180	191	400
SEI C 5000 AG	4900	Ø 180	212	400
SEI N 2000 AG	1920	125x210	132	620
SEI N 3000 AG	2790	125x290	132	620
SEI N 5000 AG	5600	183x238	214	500
SEI N 9000 AG	8650	210x285	234	620

modularni

model	Tehnički podaci			otvor
	volumen	L x L	h	Ø
	lt	cm	cm	cm
SEI M 5000 AG	4600	125x451	132	620
SEI M 7000 AG	6600	125x632	132	620
SEI M 9000 AG	8600	125x813	132	620
SEI M 12000 AG	12750	210x440	234	620
SEI M 15000 AG	14880	210x465	234	620
SEI M 18000 AG	18980	210x620	234	620
SEI M 21000 AG	21110	210x645	234	620
SEI M 24000 AG	25200	210x800	234	620
SEI M 27000 AG	27340	210x825	234	620
SEI M 30000 AG	31420	210x980	234	620
SEI M 36000 AG	37650	210x1160	234	620
SEI M 42000 AG	43870	210x1340	234	620
* SEI M 48000 AG	50100	210x1520	234	620

* montaža na mjestu ugradnje

Ovlašteni prodavatelj:

A large, empty rectangular box with a thin black border, intended for the name and address of the authorized dealer.

Uvoznik i distributer : Legomont d.o.o. www.legomont.hr

Tel: 021 533 176 Fax: 021 543 485 e-mail: legomont@legomont.hr